



Max-Chain SYNTHETIC CHAIN LUBRICANT

Royal Purple® Max-Chain® is an advanced, high performance, synthetic lubricant that provides excellent protection for chains, open gears and exposed metal surfaces subjected to severe loading — even in dusty, wet, acidic environments. Max-Chain® is a unique, thixotropic lubricant blended with a solvent carrier. When applied, Max-Chain penetrates the rollers, pins and bushings of the chain, then the carrier evaporates leaving a tenacious, dry, wax-like film. This non-tacky film effectively minimizes the collection of abrasive dust and other airborne contaminants. The EP properties of Max-Chain® greatly reduce wear and effectively extend equipment life. Max-Chain® is suitable for operating temperatures up to 400°F (after carrying solvent has evaporated) and provided excellent protection against rust and corrosion. Max-Chain® uses a non-petroleum CO2 propellant.

Synerlec® technology provides an exceptional film strength increase compared to any other comparable lubricant. The protection provided by Synerlec® dramatically reduces metal-to-metal contact and frictional wear, helping to extend power steering system component life and reduce parasitic power loss. Synerlec® also provides the lubricant with outstanding oxidation resistance to increase lubricant useful life and safely extend oil drains. The ionic attraction of Synerlec® to metal components provides unmatched wear protection, even in the absence of a full oil film.

PERFORMANCE ADVANTAGES

- SUPERIOR WEAR PROTECTION – Advanced anti-wear and EP additives greatly reduce wear and chain stretch
- DRY, NON-TACKY FILM – Applies wet and dries to a wax-like EP film; does not attract abrasive particles
- EXCELLENT CORROSION PROTECTION – Prevents surface rust, and rust between chain pins, rollers and bushings

TECH TIP

For best results shake Maxfilm® well before each use and use the can in an upright position to maximize aerosol propellant life.

Typical Physical Properties		
Property	Test Method	
Viscosity @ 40°C, cSt	ASTM D445	5.2
Viscosity @ 100°C, cSt	ASTM D445	1.7
Flash Point, °C (°F)	ASTM D92	104 (220)
Pour Point, °C (°F)	ASTM D97	-57 (-71)
Rust Prevention, Dist. Water	ASTM D665A	PASS
Rust Prevention, Sea Water	ASTM D665B	PASS
4-Ball Wear, Scar, mm	ASTM D4172	0.4

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.