

# SAFETY DATA SHEET



XPR SAE 5W-40

## Section 1. Identification

**GHS product identifier** : XPR SAE 5W-40  
**Product code** : 302195175008  
**Other means of identification** : Not available.  
**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Consumer products: Lubricating Oil Synthetic  
Industrial applications: Lubricating Oil Synthetic

#### Uses advised against

None known.

#### Reason

**Supplier's details** : Calumet Branded Products, LLC  
2780 Waterfront Pkwy E. Drive Suite 200  
Indianapolis, IN 46214  
USA  
Technical Services:317-328-5660

**Emergency telephone number** : 24 hr. CHEMTREC 1-800-424-9300 / International 1-703-527-3887

## Section 2. Hazards identification

**OSHA/HCS status** : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

**Classification of the substance or mixture** :  Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 1.5%

### GHS label elements

**Signal word** : No signal word.

**Hazard statements** :  No known significant effects or critical hazards.

### Precautionary statements

**General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** :  Not applicable.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** :  Not applicable.

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

Ingredient name	%	CAS number
Dec-1-ene, trimers, hydrogenated	≥10 - ≤22	68037-01-4
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≤10	72623-87-1
Distillates (petroleum), hydrotreated middle	≤3	64742-46-7
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	64742-56-9
Paraffin oils (petroleum), catalytic dewaxed heavy	≤2.9	64742-70-7
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	≤2	113706-15-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

## Section 4. First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** :  No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** :  In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** :  Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 nitrogen oxides  
 sulfur oxides  
 phosphorus oxides  
 metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** :  Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** :  Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Dec-1-ene, trimers, hydrogenated Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	None. <b>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated middle	<b>ACGIH TLV (United States).</b> As total hydrocarbon vapor: 200 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	<b>OSHA PEL (United States, 5/2018). [Oil mist, mineral]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist <b>OSHA PEL (United States, 5/2018). [Oil mist, mineral]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction
Distillates (petroleum), solvent-dewaxed light paraffinic	<b>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist <b>OSHA PEL (United States, 5/2018). [Oil mist, mineral]</b>

## Section 8. Exposure controls/personal protection

Paraffin oils (petroleum), catalytic dewaxed heavy

TWA: 5 mg/m<sup>3</sup> 8 hours.  
**ACGIH TLV (United States, 1/2022).**  
**[Mineral Oil, pure, highly and severely refined]**  
 TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction  
**NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]**  
 TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Mist  
 STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Mist  
**OSHA PEL (United States, 5/2018). [Oil mist, mineral]**  
 TWA: 5 mg/m<sup>3</sup> 8 hours.  
**ACGIH TLV (United States, 1/2022).**  
**[Mineral Oil, pure, highly and severely refined]**  
 TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction  
**NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]**  
 TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Mist  
 STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Mist  
 None.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoctyl) esters, zinc salts

### Biological exposure indices

None known.

### Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

##### Hand protection

:  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

##### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 8. Exposure controls/personal protection

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

**Physical state** : Liquid.  
**Color** : Purple.  
**Odor** : Not available.  
**Odor threshold** : Not available.  
**pH** : Not available.  
**Melting point/freezing point** : Not available.  
**Boiling point, initial boiling point, and boiling range** : Not available.  
**Flash point** : Open cup: 210°C (410°F) [Cleveland]  
**Evaporation rate** : Not available.  
**Flammability** : Not available.  
**Lower and upper explosion limit/flammability limit** : Not available.  
**Vapor pressure** :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
vinyl acetate	84.76	11.3				
benzene	75.01	10				
toluene	23.17	3.1				
ethylenediamine	10.5	1.4				
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed light paraffinic	<0.08	<0.011	ASTM D 5191			
Paraffin oils (petroleum), catalytic dewaxed heavy	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy naphthenic	<0.08	<0.011	ASTM D 5191			
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			
naphthalene	0.054	0.0072	OECD 104			

## Section 9. Physical and chemical properties and safety characteristics

Solvent naphtha (petroleum), heavy arom.	0.02	0.0027				
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	0.000052	0.0000069	EU A.4	0.0003	0.00004	EU A.4
Dec-1-ene, trimers, hydrogenated	0.000000002	0.0000000027	EU A.4			
Dec-1-ene, homopolymer, hydrogenated	0	0	ASTM E 1194-87			
Synthetic Polyol Ester	0	0				
4,4'-methylene bis (dibutyldithiocarbamate)	<0	<0				

**Relative vapor density** : Not available.

**Relative density** : 0.8701

**Solubility(ies)** : Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/water** : Not applicable.

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), heavy arom.	220 to 250	428 to 482	ASTM E 659
Distillates (petroleum), hydrotreated middle	225	437	
Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
2-Butenedioic acid (E)-, di-C8-18-alkyl esters	380	716	
vinyl acetate	402	755.6	
ethylenediamine	405	761	DIN 51794
toluene	480	896	
benzene	498	928.4	
naphthalene	526 to 587	978.8 to 1088.6	DIN 51794

**Decomposition temperature** : Not available.

**Viscosity** : Kinematic (40°C (104°F)): 61.27 mm<sup>2</sup>/s (61.27 cSt)

**Flow time (ISO 2431)** : Not available.

**Pour point** : -44°C (-47.2°F)

### Particle characteristics

**Median particle size** : Not applicable.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : No specific data.

**Incompatible materials** : No specific data.

## Section 10. Stability and reactivity

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dec-1-ene, trimers, hydrogenated Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
Distillates (petroleum), hydrotreated middle	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-
Distillates (petroleum), hydrotreated heavy paraffinic	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
Distillates (petroleum), solvent-dewaxed light paraffinic	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
Paraffin oils (petroleum), catalytic dewaxed heavy	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoocetyl) esters, zinc salts	LD50 Dermal	Rabbit - Male, Female	>3160 mg/kg	-
	LD50 Oral	Rat	2600 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoocetyl) esters, zinc salts	Eyes - Severe irritant	Rabbit	-	504 hours	-
	Skin - Irritant	Guinea pig	-	4 hours	-

#### Sensitization

Product/ingredient name	Route of exposure	Species	Result
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoocetyl) esters, zinc salts	skin	Guinea pig	Not sensitizing

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.



## Section 11. Toxicological information

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
Dec-1-ene, trimers, hydrogenated	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated middle	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

## Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
XPR SAE 5W-40	9374.2	4069.9	N/A	N/A	N/A
Dec-1-ene, trimers, hydrogenated	2500	N/A	N/A	N/A	N/A
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated middle	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	2500	N/A	N/A	5.7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed light paraffinic	N/A	2500	N/A	N/A	N/A
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	2500	N/A	N/A	N/A
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	2600	2500	N/A	N/A	N/A

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Dec-1-ene, trimers, hydrogenated	Acute NOEC 2 mg/l (similar material)	Micro-organism	28 days (similar material)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EC50 >100 mg/l	Algae	72 hours
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Crustaceans	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute IC50 >100 mg/l	Algae	72 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Acute EC50 >100 mg/l	Algae	72 hours
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Chronic NOEL >1 mg/l	Daphnia	21 days
	LC50 4.5 mg/l	Fish	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	OECD 301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	1.5 % - Not readily - 28 days	-	-
	OECD 301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	1.5 % - Not readily - 28 days	-	-

## Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Dec-1-ene, trimers, hydrogenated	-	-	Not readily
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Inherent
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoctyl) esters, zinc salts	-	-	Not readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dec-1-ene, trimers, hydrogenated	>6.5	-	high
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	>6	-	high
Distillates (petroleum), hydrotreated heavy paraffinic	>6	-	high
Distillates (petroleum), solvent-dewaxed heavy paraffinic	2 to 6	-	high

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 4(a) final test rules: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters  
 TSCA 8(a) PAIR: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters; naphthalene  
 TSCA 8(a) CDR Exempt/Partial exemption: Not determined  
 Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts; Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts; toluene; benzene  
 Clean Water Act (CWA) 311: toluene; benzene; ethylenediamine

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

### SARA 302/304

#### Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
<input checked="" type="checkbox"/> ethylenediamine	<0.1	Yes.	10000	1337.1	5000	668.5
vinyl acetate	<0.1	Yes.	1000	129	5000	644.8

SARA 304 RQ :  4984013.9 lbs / 29502742.3 kg [8957361.2 gal / 33907300.7 L]

### SARA 311/312

Classification : Not applicable.

#### Composition/information on ingredients

Name	%	Classification
<input checked="" type="checkbox"/> Dec-1-ene, trimers, hydrogenated	≥10 - ≤22	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated middle	≤3	FLAMMABLE LIQUIDS - Category 4 ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	ASPIRATION HAZARD - Category 1
Phosphorodithioic acid, mixed O, O-bis(sec-Bu and isooctyl) esters, zinc salts	≤2	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

### SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	<input checked="" type="checkbox"/> Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	≤2
Supplier notification	<input checked="" type="checkbox"/> Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	≤2

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

Massachusetts :  None of the components are listed.

New York : None of the components are listed.

## Section 15. Regulatory information

- New Jersey** : The following components are listed: ZINC compounds  
**Pennsylvania** : The following components are listed: ZINC COMPOUNDS  
**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Information provided is based on industrial use and may not be relevant to consumer applications.

Ingredient name	Concentration (%)	No significant risk level	Maximum acceptable dosage level
Toluene	0.0146	-	Yes.
Benzene	0.0146	Yes.	Yes.

### International lists

#### National inventory

- Australia** : All components are listed or exempted.  
**Canada** : All components are listed or exempted.  
**China** : All components are listed or exempted.  
**Eurasian Economic Union** : **Russian Federation inventory:** Not determined.  
**New Zealand** : All components are listed or exempted.  
**Philippines** : All components are listed or exempted.  
**Republic of Korea** : All components are listed or exempted.  
**Taiwan** : Not determined.  
**Thailand** : Not determined.  
**Turkey** : Not determined.  
**United States** : All components are active or exempted.  
**Viet Nam** : Not determined.

## Section 16. Other information

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (LONG-TERM) - Category 4	Calculation method

### History

- Date of issue/Date of revision** : 12/14/2022  
**Date of previous issue** : 08/25/2022  
**Version** : 4

## Section 16. Other information

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

▣ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.